



# CERAMICA RIBESALBES

PAVIMENTO Y REVESTIMIENTO CERÁMICO

## TECHNICAL SHEET

**PRODUCT: APPLIES FOR ALL PRODUCTS PORCELAIN SIZE CM.  
20X20 UPON NORM UNE-EN-ISO 10545**

- DRY PRESS CERAMIC TILES GLAZED
- WORK SIZE IN MM: 200.5X200.5 ±0,6%
- WORK SIZE THICKNESS IN MM: 8.0 ± 5%
- STRAIGHTNESS DEVIATION INSIDE THE NORM
- WATER ABSORPTION: 0,28%
- SURFACE ABRASION: CLASS 4
- HOUSEHOLD CHEMICALS: GA
- SWIMMING POOL SALTS: GA
- ACIDS AND ALKALIS ( LOW CONCENTRATIONS ): GLA
- ACIDS AND ALKALIS ( HIGH CONCENTRATIONS ): GHA
- STAINS HAVING TRACING ACTIONS: CLASS 5
- STAINS HAVING CHEMICAL OXIDIZING ACTION: CLASS 5
- STAINS HAVING FILMING ACTIONS: CLASS 5
- MOSH HARDNESS: 5
- SLIP RESISTANCE CLASS: R-10, CLASS 2.
- GROUP BIa STANDARD UNE - EN 14411

Onda, 21-03-24

**CERAMICA  
RIBESALBES, S.A.**  
Ctra. Onda-Ribesalbes, km 3,300  
12200 ONDA (Castellón)