

Nanotech Columbia 45x45

PORCELÁNICO ESMALTADO / GLAZED PORCELAIN TILE



Sand



Pearl



Grey



Dark Grey

FORMATO / SIZE

45x45 / 17³/₄ "x 17³/₄ "

ACABADO/FINISH

Mate / Matt



NANOTECH
NANOTECH



MATE
MATT



PORCELÁNICO
PORCELAIN



CEMENTO
CEMENT



ANTIHIELO
ANTIFREEZE



VARIACIÓN
VARIATION

GRUPO / GROUP

Bla

TIPO/ TYPE

Cemento / Cement

DESCRIPCIÓN DEL TEST / TEST DESCRIPTION		VALOR DEL TEST / TEST VALUE		NORMA / STANDARD
Absorción de agua / Water absorption		Ev≤ 0,5%	Cumple / Complies	UNE-EN ISO 10545-3
Fuerza de rotura / Breaking Strength		≥1300 N	Cumple / Complies	UNE-EN ISO 10545-4
Resistencia a la flexión / Modulus of rupture		≥ 35 N/mm2	Cumple / Complies	UNE-EN ISO 10545-4
Abrasion superficial / Surface Abrasion		PEI Clase 3 / Class 3- Pearl; Sand PEI Clase 2 / Class 2- Grey, D.Grey	Valor declarado / Declared value	UNE-EN-ISO 10545-7
Resistencia al cuarteo / Crazeing resistance		Requerido / Requested	Cumple / Complies	UNE-EN ISO 10545-11
Resistencia a la helada / Frost resistance		Requerido / Requested	Cumple / Complies	UNE-EN ISO 10545-12
Resistencia al deslizamiento / Slip resistance		Ensayo del péndulo/ Pendulum test	Clase 3 / Class 3	UNE-EN 16165 Anexo C AN 2.6
		Resistencia al deslizamiento (Péndulo): Método operativo (PTV) /Slip resistance (Pendulum): Pendulum test value(PTV)	+36	UK SRG
		Coefficiente de fricción dinámico (D.C.O.F)/ Dynamic coefficient of friction (D.C.O.F)	>0.63	ANSI A137.1-2021
		Método de la rampa con Pie descalzo/ Shod Ramp Test	≥R10	UNE-EN 16165 Anexo B AN 3.3
		Método de la rampa con Pie descalzo/ Barefoot Ramp Test	Clase C / Class C	UNE-EN 16165 Anexo A AN 3.2
Resistencia química / Chemical resistance	Productos domésticos y de piscina / Household chemicals and swimming pool salts	Mínimo clase B / Minimum class B	Cumple / Complies	UNE-EN ISO 10545-13
	Ácidos a baja concentración / Low concentration of acids	Mínimo clase LB / Minimum class LB	Valor declarado / Declared value	UNE-EN ISO 10545-13
	Bases a baja concentración / Low concentration of alkalis	Mínimo clase LB / Minimum class LB	Valor declarado / Declared value	UNE-EN ISO 10545-13
Resistencia a las manchas / Stain resistance		Mínimo clase 3 / Minimum Class 3	Cumple / Complies	UNE-EN ISO 10545-14

12/06/2024

Partida Casablanca 6, 12593 Moncofar, Castellón . Spain
Phone : +34 964 584 069 - email: info@ktlceramica.com - web : www.ktlceramica.com

KTL
CERAMICA